



BNC Type Male Conn.

ITEM	DESCRIPTION	MATERIAL	FINISH	Q'TY
9	FERRULE	BRASS	NICKEL	1
8	WASHER	BRASS	NICKEL	1
7	SPRING	BRASS	NICKEL	1
6	Retainer Ring	SK-5	NICKEL	1
5	GASKET	RUBBER	RED	1
4	INSULATOR	DELIRIN	NONE	1
3	PIN	BRASS	GOLD	1
2	SHELL	ZINC	NICKEL	1
1	BODY	BRASS	NICKEL	1



SPECIFICATION

PERFORMANCE PROPERTIES											
IMPEDANCE		75 ±5 Ω									
CAPACITANCE		53.5 pF / M Nom.									
VELOCITY OF PROPAGATION		83% Nom.									
ATTENUATION (at 100M)	MHZ	5	42	55	65	70	211	216	240	270	300
	dB	3.0	7.5	8.5	9.2	9.8	15.4	15.8	16.7	17.7	18.6
ATTENUATION (at 100M)	MHZ	325	350	375	400	450	500	550	600	650	700
	dB	19.4	20.0	20.8	21.5	22.9	24.2	25.6	27.3	28.9	30.4
ATTENUATION (at 100M)	MHZ	750	800	862	870	900	950	1000	1500	2250	3000
	dB	31.5	32.1	32.8	33.1	33.5	33.8	34.4	42.6	52.5	60.7
DIELECTRIC STRENGTH TEST		1KV(AC)/1min.Min.									

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X, ±
X, ±
.XX ±
.XXX ±
ANG ±

PJECTION



ORDER INFORMATION

BNCX2-1S1S3G59-M1M-LF

SERIES

LEADFREE

1000mm

MALE TO MALE

3G RG 59

ST/ST

DESCRIPTION:

煜倫股份有限公司

www.morethanall.com