

RECOMMENDED PCB LAYOUT

- \* Material : Nylon UL 94V -2
- \* Current rating : 1A, AC/DC
- \* Voltage rating : 250V AC/DC
- \* .025" (0.64mm) straight square pins
- \* Tin plated brass pins, plating optional
- \* Various pin length available
- \* Friction lock
- \* 2-20 circuits available

**RK-D-xx-LF**  
**LEADFREE**  
**RoHS Compliant**

Dimensional information -inch/mm

Circuits	Dim. A		Dim. B		Circuits	Dim. A		Dim. B	
	inch	mm	inch	mm		inch	mm	inch	mm
2	0.098	2.50	0.197	5.00	12	1.083	27.50	1.181	30.00
3	0.197	5.00	0.295	7.50	13	1.181	30.00	1.280	32.50
4	0.295	7.50	0.394	10.00	14	1.280	32.50	1.378	35.00
5	0.394	10.00	0.492	12.50	15	1.378	35.00	1.476	37.50
6	0.492	12.50	0.591	15.00	16	1.476	37.50	1.575	40.00
7	0.591	15.00	0.689	17.50	17	1.575	40.00	1.673	42.50
8	0.689	17.50	0.787	20.00	18	1.673	42.50	1.772	45.00
9	0.787	20.00	0.886	22.50	19	1.772	45.00	1.870	47.50
10	0.886	22.50	0.984	25.00	20	1.870	47.50	1.969	50.00
11	0.984	25.00	1.083	27.50					



PART NO. **RK-D-xx**

DWG NO. **RK-D-xx**

FILE NO.


UNIT / mm

SCALE 1:1

CHECKED BY CY

DRAWING BY

PROJECTION



TOLERANCES ARE

.X ± 0.2  
 .XX ±  
 .XXX ±  
 AWG

DESCRIPTION:

AREA

REVISIONS

HK

DATE

煜倫股份有限公司