

## SPECIFICATIONS

### Electrical

Current Rating: 7A AC, DC

Voltage Rating: 250V AC, DC

Operating Temp.: -25°C ~ +85°C

Insulation Resistance: 1000M $\Omega$ / min.

Dielectric Withstanding Voltage: 1500V AC/ min.

Contact Resistance: 10m $\Omega$ / max.

### Material

Material: Nylon66, UL94V-2

Poles	Dimension mm (in.)		Part No.	Note.
	A	B		
2	5.08	10.30	LKX-R-02	
3	10.16	15.40	LKX-R-03	
4	15.24	20.50	LKX-R-04	
5	20.32	25.60	LKX-R-05	
6	25.40	30.70	LKX-R-06	
7	30.48	35.80	LKX-R-07	
8	35.56	41.00	LKX-R-08	
9	40.64	46.10	LKX-R-09	
10	45.72	51.20	LKX-R-10	
11	50.80	56.30	LKX-R-11	
12	55.88	61.40	LKX-R-12	

**RoHS Compliant**

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT/ mm


SCALE 1:1

DATE

SIZE A4

P PROJECTION

X,  $\pm$   
.X  $\pm$  0.50  
.XX  $\pm$  0.10  
.XXX  $\pm$   
ANG  $\pm$



**ORDER INFORMATION**

LKX-R-xx-LF  
SERIES | 02-12WAY | LEADFREE  
DIP 90°

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: 5.08mm Wire-to-Board Header Dip 90° Type