



MATERIALS

HOUSING: HI-TEMP. PLASTIC (UL 94V-0)
 SHELL: STAINLESS STEEL, TIN PLATING
 TERMINAL: COPPER ALLOY, GOLD PLATED

SPECIFICATION

CURRENT RATING: 0.5 AMP MAX (ONLY PIN 1, 5), OTHER 1 AMP MAX
 DIELECTRIC WITHSTANDING: 100V AC FOR ONE MINUTE
 CONTACT RESISTANCE: 30m OHMS MAX
 INSULATION RESISTANCE: 100M OHMS MIN AT DC 500V
 OPERATION TEMPERATURE: -25°C~+105°C

MISB-SWE-10B-LF
LEADFREE
RoHS Compliant

P.B.C LAYOUT
 TOP VIEW ±0.05

MORETHANALL
 CONNECTORS
 ASSEMBLIES

PART NO. MISB-SWE-10B

DWG NO. MISB-SWE-10B

CHECKED BY CY

TOLERANCES ARE

DESCRIPTION: MICRO USB 3.0 B TYPE, PCB MOUNT, SMT, METAL SHIELD

煜倫股份有限公司

FILE NO.

DRAWING BY

.X ± 0.2
 .XX ±
 .XXX ±
 AWG

UNIT / mm

SCALE 1:1

PROJECTION

AREA	REVISIONS	HK	DATE
------	-----------	----	------