

RECOMMENDED P.C.B LAYOUT(TOP VIEW)
TOLERANCES: ±0.10mm

△ SPECIFICATION

MATERIAL

Insulator: PBT, rated UL94V-0 (standard)
Contacts: Brass (Male)
Phosphor Bronze (Female)

Shell: Steel

Rivet, Boardlock: Copper alloy

△ CONTACT PLATING

Underplate: 50u" Nickel
Contact area: 1u"~30u" Selective Gold
Solder tails area: 100u" Tin/Lead

ELECTRICAL

Operation voltage: 250 VAC max.
Current rating: 1 Amps max.
Contact resistance: 20 mohms max.
Insulation resistance: 1000 Mohms min @ 500 VDC
Dielectric withstanding voltage: 1000 VAC / minute
Operating temperature: -55°C TO +125°C

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm


SCALE 1 : 1

DATE

SIZE A4

PJECTION

X. ±
.X ±
.XX ±
.XXX ±
ANG ±



ORDER INFORMATION

UB-PD-2X32-LF
SERIES | LEADFREE
DIP 180°
64WAY
MALE

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: DIN 41612 MALE 64 PIN