

RECOMMEND P.C.B. LAYOUT  
TOP VIEW

## MATERIALS

1. HOUSING : NYLON 6T (UL 94V-0), BLACK.
2. TERMINAL : S.Q. 0.64mm BRASS, GOLD PLATING.

## SPECIFICATION

1. CURRENT RATING : 3 AMP. MAX.
2. DIELECTRIC WITHSTANDING VOLTAGE : 1000V AC R.M.S. FOR ONE MINUTE.
3. INSULATION RESISTANCE : 5000M OHMS MIN. AT 1000V DC.
4. OPERATING TEMPERATURE : -55°C TO +105°C.
5. MAX. PROCESSING TEMPERATURE : 230°C FOR 30 ~ 60 SECONDS.

NUMBER OF POSITION	DIMENSIONS			NUMBER OF POSITION	DIMENSIONS		
	A	B	C		A	B	C
6	15.24	12.94	5.08	26	40.64	38.34	30.48
8	17.78	15.48	7.62	30	45.72	43.42	35.56
10	20.32	18.02	10.16	34	50.80	48.50	40.64
12	22.86	20.56	12.70	40	58.42	56.12	48.26
14	25.40	23.10	15.24	44	63.50	61.20	53.34
16	27.94	25.64	17.78	50	71.12	68.82	60.96
20	33.02	30.72	22.86	60	83.82	81.52	73.66
24	38.10	35.80	27.94	64	88.90	86.60	78.74

**RoHS Compliant**

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT/mm SCALE 1:1

DATE


SIZE A4

X. ±  
.X ±  
.XX ±  
.XXX ±  
ANG ±

PJECTION



**ORDER INFORMATION**



煜倫股份有限公司

www.morethanall.com

DESCRIPTION: 2.54mm SHROUDED HEADER SMT