



PACKING:
20 PCS/BIND

NOTES:

1. ALL DIMENSIONS ARE "mm".
2. THE PRODUCT MUST BE COMPLY WITH THE DIRECTIVE OF ROHS.

ELECTRICAL TESTING:

1. 100% OPEN/SHORT TEST
2. CONTACT RESISTANCE: 5mΩ
3. INSULATION RESISTANCE: 5MΩ Min

NO.	ITEM.	DESCRIPTION	Q'TY	UL/CSA No.
1	WIRE:	UL1007 #24 BLACK	13PCS	E108485
2	WIRE:	UL1007 #24 YELLOW	1PCS	E108485
3	WIRE:	UL1007 #24 BLUE	1PCS	E108485
4	WIRE:	UL1007 #24 RED	1PCS	E108485
5	HOUSING:	MKL-HWH-06 WHITE	1PCS	E144544
6	HOUSING:	MKL-HWH-10 WHITE	1PCS	E144544
7	HOUSING:	MKL-HWH-16 WHITE	1PCS	E144544
8	TERMINAL:	MKL-T-22	32PCS	E144544

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X, ±
.X ±
.XX ±
.XXX ±
ANG ±

PJECTION



ORDER INFORMATION

MK LX12-16061024WH-F21C-LF

SERIES

LEADFREE
210mm
FEMALE TO FEMALE
WHITE
24 AWG
16,06,10 WAY

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: CABLE ASS'Y