

Material

- Item 1 Insulating body Thermoplastic (UL94V-0)
- Item 2 Insulating cover Thermoplastic (UL94V-0)
- Item 3 Insulating lever Thermoplastic (UL94V-0)
- Item 4 Contact pin Brass, Tin plated
- Item 5 Spring clamp Stainless steel

Electrical cULus

- Voltage rating:300V
- ▲ ▲ ● Current rating:8A
- Wire range:
- Solid wire(AWG):16-26
- Stranded wire(AWG):16-26
- Wire strip length:6-7mm
- Withstanding Voltage:1.6KV
- ▲ ● Operating temperature:-40°C to +115°C
- ▲ ● Soldering temperature:250°C±10°C/5 Sec
- Safety Approval:
- Critical dimension:

N=NUMBER OF POLES

Dim L	(N-1)×5.0+6.0
Dim B	(N-1)×5.0

	TOL				
	1--4P	5--9P	10--14P	15--19P	20--24P
Dim L	±0.15	±0.20	±0.30	±0.40	±0.50
Dim B	±0.15	±0.20	±0.30	±0.40	±0.50

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

X. ± 0.50


.X ± 0.30

.XX ± 0.10

.XXX ±

ANG ±

P PROJECTION



ORDER INFORMATION

TBX050-D15A-xx-LF

SERIES

LEADFREE

01-24WAY

DSLANT

HIGH 15.5mm

DIP180°

DESCRIPTION: