

Note:

1.Material:

- 1.1 Insulator: P.B.T UL 94-V0 rated.
- 1.2 Contact: Brass,t=0.20mm.
- 1.3 Shell: Cold rolled steel,t=0.40mm.

2.Specification:

- 2.1 Current rating: 1 A Max.
- 2.2 Dielectric withstanding voltage: 500 V(ac) for 1 minute.
- 2.3 Contact resistance: 30 mΩ Max.
- 2.4 Insulation resistance: 1000 MΩ Min at DC 500V.
- 2.5 Temperature range: -55°C~+105°C

3.Finishes:

- 3.1 Contacts:Gold flashed 1u",3u",5u",10U",15u",30u".
- 3.2 Shell: Nickel,tin or gold plated

PART NO	A±0.25	B±0.25	C±0.25	D±0.25	E±0.25	G±0.25	H±0.20	I±0.20
HDD-PGN-15	30.80	25.00	16.92	8.30	17.00	12.60	2.29	3.96
HDD-PGN-26	39.20	33.32	25.25	8.30	17.00	12.60	2.29	3.96
HDD-PGN-44	53.05	47.04	38.96	8.30	17.00	12.60	2.29	3.96
HDD-PGN-62	69.40	63.50	55.42	8.30	17.00	12.60	2.41	3.96

RoHS Compliant

TOLERANCES ARE



DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X, ±


.X ±

.XX ±


.XXX ±

ANG ±

PPOJECTION



ORDER INFORMATION



DESCRIPTION:

煜倫股份有限公司

www.morethanall.com