


DIP TYPE



- MATERIAL  
INSULATOR: PBT +30% GLASS FIBER (UL94V-0).  
CONTACT: PHOSPHOR BRONZE OR BRASS.  
PLATING: GOLD OVER NICKEL.

- SPECIFICATION  
CURRENT RATING: 3 AMP.  
INSULATION RESISTANCE: 5000 MEGOHMS MIN AT 500 VDC.  
CONTACT RESISTANCE: 20 MILLIOHMS MAX.  
VOLTAGE : 500V FOR ONE MINUTE.

- ENVIRONMENTAL  
TEMPERATURE RANGE: -40°C TO +105°C.

Circuit	Dimension		
	A	B	C
10	15.84	24.06	27.40
12	19.80	28.02	31.36
16	27.72	35.94	39.28
20	35.64	43.86	47.20
24	43.56	51.78	55.12
26	47.52	55.74	59.08
28	51.48	59.70	63.04
30	55.44	63.66	67.00
32	59.40	67.62	70.96
36	67.32	75.54	78.88
40	75.24	83.46	86.80
44	83.16	91.38	94.72
46	87.12	95.34	98.68
50	95.04	103.26	106.60
56	106.92	115.14	118.48
60	114.84	123.06	126.40
62	118.80	127.02	130.36
64	122.76	130.98	134.32
70	134.64	142.86	146.20
72	138.60	146.82	150.16

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm


SCALE 1 : 1

DATE

SIZE A4

PJECTION

X. ±  
.X ±  
.XX ±  
.XXX ±  
ANG ±



ORDER INFORMATION

KE-DXE BK-xx-LF  
SERIES | LEADFREE  
| 10-72 WAY  
| BLACK  
| NON EAR  
| DIP 180°

DESCRIPTION: 3.96 PITCH WITH OUT MOUNTING EAR