



**SPECIFICATION**

**MATERIAL**

Insulator: Polyester resin and glass fiber reinforced (UL 94V-0)

Contacts: Brass

**CONTACT PLATING**

Underplate: 50u" Nickel

Contact area: 1u"~30u" Selective gold

Solder tails area: 100u" Tin/Lead

**ELECTRICAL**

Operation voltage: 250 VAC max.

Current rating: 3 Amps max.

Contact resistance: 15 mohms max.

Insulation resistance: 3000 Mohms min @ 500 VDC

Dielectric withstanding voltage: 1000 VAC / minute

Operating temperature: -55°C TO +105°C

POSITION	A	B	C	D
DFM-P-09	16.92	25.00	30.8	22.4
DFM-P-15	25.25	33.30	39.2	30.8
DFM-P-25	38.96	47.10	53.1	44.5
DFM-P-37	55.42	63.50	69.4	61.4

DFM-P-xx-LF

└

LEADFREE

RoHS Compliant

**MORETHANALI**  
CONNECTORS  
ASSEMBLIES

PART NO. DFM-P-xx

DWG NO. DFM-P-xx

CHECKED BY CY

TOLERANCES ARE

DESCRIPTION:

D-SUB IDC FOR FLAT RIBBON CABLE

FILE NO.

DRAWING BY

.X ± 0.3  
.XX ± 0.2  
.XXX  
AWG

AREA

REVISIONS

HK

DATE

焯倫股份有限公司

UNIT / mm

SCALE 1:1

PROJECTION

