



B-B

NOTE:

1. 表面處理
預鍍錫 40u"以上

1. SURFACE TREATMENT:
PRE-TIN
THICKNESS MORE THAN 40u"

| | | | | | | |
|-----------------|---------|---------------------------|-------------------------------------|-----------------------------|-------------|-----|
| 材質 MATERIAL | JIS2680 | 一般公差 GENERAL TOLERANCE | X : ±0.5 XX : ±0.3 XXX : ±0.1 | X.XXX : ±0.05 ANGLES ±3° | 比例 SCALE | 3:1 |
| 料厚 THICKNESS | 0.3 | 包裝數量 PACKING Q'TY | 4000 PCS/R | 適用電線 WIRE RANGE | 22~16 | |
| 間距 PITCH | 14.35 | 對手件 MATING PART | TAB=0.8 | | | |

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1:1

DATE

SIZE A4

PJECTION

X, ±
.X ±
.XX ±
.XXX ±
ANG ±



ORDER INFORMATION

Q187-GT8LS-16-LF

SERIES LEADFREE
16~22AWG
SPRING
LOCKING
FLAG 0.8t
TERMINAL

DESCRIPTION: