

SEC A-A

E-RME-xxx-LF
LEADFREE
RoHS Compliant

FEATURE:

INSULATOR

Glass-Filled P.B.T. is 94V-0 rated

CONTACT

Phosphor Bronze selective gold plating
over nickel

SPECIFICATION:

Current Rating . 3 amperes

Contact Resistance . 20 miniohms max

Operation Temperature -55°c to +105°c

Voltage Rating . 800 VAC 1 minute

Insulation Resistance . 5000 megaohms min

Insertion Force . 412 grams max per pair

Withdrawal Force . 32 grams min. per pair

CONTACT NO	DIM A	DIM B	DIM C	DIM D	DIM E
12/24	51.69	45.09	37.38	33.22	27.94
22/44	77.09	70.49	62.78	58.62	53.34
24/48	82.17	75.57	67.86	63.70	58.42
25/50	84.71	78.11	70.40	66.24	60.96
28/56	92.33	85.73	78.02	73.86	68.58
30/60	97.41	90.81	83.10	78.94	73.66
35/70	110.11	103.51	95.80	91.64	86.36
36/72	112.65	106.05	98.34	94.18	88.90
43/86	131.43	123.83	116.12	111.96	106.68
44/88	133.17	126.57	118.66	114.50	109.22
50/100	148.21	141.61	133.90	129.74	124.46

MORETHANALL
CONNECTORS
ASSEMBLIES

PART NO. E-RME-xxx

DWG NO. E-RME-xxx

FILE NO.


UNIT / mm

SCALE 1:1

CHECKED BY CY

DRAWING BY

PROJECTION



TOLERANCES ARE

.X ± 0.2

.XX ± 0.1

.XXX ±
AWG

DESCRIPTION:

EDGE CONNECTOR 2.54mm PITCH
WITH MID-HIGH MOUNTING EARS
R/A TYPE

AREA

REVISIONS

HK

DATE

焜倫股份有限公司