

Material

- Item ① Clamp: Brass(CuZn) Ni plated
- Item ② Terminal screw: Steel Zinc plating "-" slot type
- Item ③ Female contact: PhBz ,Tin plated
- Item ④ Terminal Cover: Thermoplastic (UL94V-0)
- Item ⑤ Terminal housing: Thermoplastic (UL94V-0)

Electrical cULus

- Voltage rating: 300VAC
- Current rating: 20A
- Wire range: 2.5mm²
- Solid wire(AWG): 12-24
- Stranded wire(AWG): 12-24
- Torque: 5Lb-In
- Screw: M3
- Wire strip length: 7-8mm
- Withstanding Voltage: 1.6KV
- Operating temperature: -40°C to +115°C
- Safety Approval: us

N = Number of poles
 Dim A=(N-1)X7.62+5.62
 Dim B=(N-1)x7.62

	Dim A	Dim B
2-4p	±0.15	±0.15
5-8p	±0.20	±0.20
9-12p	±0.30	±0.30
13-16p	±0.40	±0.40

RoHS Compliant

TOLERANCES ARE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT/mm SCALE 1:1

DATE


SIZE A4

X. ± 0.50
 .X ± 0.30
 .XX ± 0.10
 .XXX ±
 ANG ± 1°

PJECTION



ORDER INFORMATION



DESCRIPTION: