



SPECIFICATION:

PITCH BETWEEN POLES : 1.0mm
 CURRENT RATING : 1A AC/DC
 VOLTAGE RATING : 100V AC/DC
 CONTACT RESISTANCE : 30mΩ (max.)
 INSULATION RESISTANCE : 500MΩMIN
 WITHSTAND VOLTAGE : 300V AC/MINUTE
 TEMPERATURE RANGE : -25°C TO +85°C
FEATURES:
 AVAILABLE NUMBER OF CIRCUITS : 8 TO 30
 MATERIAL : NYLON 9T UL 94V-0
 CONTACT : 0.20mm(.008") FLAT PIN ,
 PHOSPHOR BRONZE, SEMI-GLOSS TIN

DF19-W-xx-LF
 LEADFREE
 RoHS Compliant

Dimensional and Order Information

Poles	Part No	DIM:(mm)	
		A	B
8	DF19-W-08	7.00	11.55
14	DF19-W-14	13.00	17.55
20	DF19-W-20	19.00	23.55
30	DF19-W-30	29.00	33.55



煜倫股份有限公司

PART NO. DF19-W-xx		CHECKED BY CY	TOLERANCES ARE .X ± 0.2 .XX ± .XXX ± AWG	DESCRIP TION:			
DWG NO. DF19-W-xx							
FILE NO.		PROJECTION	AREA	REVISIONS	HK	DATE	
UNIT / mm	SCALE 1:1						