

- \* Material : Nylon UL 94V-0
- \* Current rating : 2A, AC/DC
- \* Voltage rating : 125V, AC/DC
- \* Standard color: Tan
- \* 2-15 circuits available

Dimensional information - inch/mm

Circuits	Dim. A		Dim. B		Circuits	Dim. A		Dim. B	
	inch	mm	inch	mm		inch	mm	inch	mm
2	0.098	2.50	0.256	6.50	9	0.787	20.00	0.945	24.00
3	0.197	5.00	0.354	9.00	10	0.886	22.50	1.043	26.50
4	0.295	7.50	0.453	11.50	11	0.984	25.00	1.142	29.00
5	0.394	10.00	0.551	14.00	12	1.083	27.50	1.240	31.50
6	0.492	12.50	0.650	16.50	13	1.181	30.00	1.339	34.00
7	0.591	15.00	0.748	19.00	14	1.280	32.50	1.437	36.50
8	0.689	17.50	0.846	21.50	15	1.378	35.00	1.535	39.00

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm


SCALE 1 : 1

DATE

SIZE A4

PPOJECTION

X, ±  
.X ±  
.XX ±  
.XXX ±  
ANG ±



ORDER INFORMATION

SCN-H-xx-LF  
SERIES | LEADFREE  
02~15WAY  
HOUSING

DESCRIPTION: SCN series Crimp Terminal Housings