

Position

	A	B	C	D
24	23.76	49.3	35.5	37.50
36	36.72	62.0	51.5	53.75
50	51.84	77.4	68.5	70.90

Material & Finish

SHELL:

Steel
Zinc plated, Tin plated
or Nickel plated steel

PIN CONTACT:

Phosphor bronze or Brass
Gold Flash

INSULATOR:

PBT & Glass-fibre reinforced
UL-94-V0

NUMBER OF CONTACT:

14,24,36,50

DURABILITY

100 cycles

CURRENT RATING:

1 Amp

DIELECTRIC STRENGTH:

AC 1000V Min.(for one minute)

INSULATOR RESISTANCE:

1000MΩ Min. (at 500V DC)

CONTACT RESISTANCE

25m Max. mated

TEMPERATURE:

-55° C to +105° C

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm


SCALE 1:1

DATE

SIZE A4

PPOJECTION

X. ±
.X ±
.XX ±
.XXX ±
ANG ±



ORDER INFORMATION

CFM-P-xx-LF
SERIES | T LEADFREE
24~50 WAY
MALE

DESCRIPTION:

煜倫股份有限公司

www.morethanall.com