



MATERIALS:

- A.BOOT: PE + 2L
- B.MIDDLE HOOD: PA-757/ PS-475
- C.METAL SHELL:
COPPER NICKEL PLATED
- D.INSULATOR: NYLON 6 + G.F.
- E.PIN CONTACT:
BRASS GOLD FLASH

SPECIFICATIONS:

- 1.RATION: 100V AC 1A MAX or 12V DC 2A MAX.
2. INSULATION RESISTANCE: 50M OHM MIN at 250V DC.
3. DIELECTRIC STRENGTH: 250 V AC / 1 MINUTE.
4. CONTACT RESISTANCE: 30M OHM MAX.
5. INSERTION FORCE: 4.5KG MAX.
6. WITHDRAWAL FORCE: 0.9KG ~ 3KG.
7. OPERATING TEMPERATURE: -20°C ~ 105°C

<input type="checkbox"/>	7.0Ø BACK SHELL
<input type="checkbox"/>	6.0Ø BACK SHELL
<input checked="" type="checkbox"/>	5.0Ø BACK SHELL (STANDARD)
<input type="checkbox"/>	COVER DIM.

TABLE A

RoHS Compliant

TOLERANCES ARE



煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

- X, ±
- .X ±
- .XX ±
- .XXX ±
- ANG ±

P PROJECTION



ORDER INFORMATION

MDL-J-xx-LF
SERIES | LEADFREE
03-08 WAY
JACK

NON POST

DESCRIPTION: Mini Din Jack Lock Ass'y Type