



1. MATERIAL :
 - 1-1. NY-WP494 :
 - a. HOUSING : PBT UL94V-0 ; COLOR : BLACK.
 - b. CONTACT : BRASS
 - c. NUT : ALUMINUM ALLOY
 - d. SHELL : ALUMINUM ALLOY
 - e. Epoxy Base : EF400A&EF400B. COLOR : BLACK.
 - 1-2. Main Body : ALUMINUM ALLOY
 - 1-3. Gland : SILICONE COLOR : BLACK.
 - 1-4. Gland Cage : POM ; COLOR : BLACK.
 - 1-5. Gland Nut : ALUMINUM ALLOY.
2. FINISH :
 - 2-1. NY-WPXXX :
 - a. CONTACT : GOLD FLASH MICRO INCHES MIN. UNDER PLATE : NICKEL.
 - b. NUT : SATING Ni PLATED.
 - c. SHELL : SATING Ni PLATED.
 - 2-2. Main Body : SATING Ni PLATED.
 - 2-3. Gland Nut : SATING Ni PLATED.
3. ELECTRICAL SPECIFICATION :
 - 3-1. Rated current : 5A
 - 3-2. Rated Voltage : 125V
 - 3-3. Water proof : IPX7
4. Environmental :
 - 4-1. Operation Temperature : -20 ℃~85℃

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1:1

DATE

SIZE A4

X, ±
.X ± 0.20
.XX ± 0.10
.XXX ± 0.05
ANG ±

PJECTION



ORDER INFORMATION

M12-PA-04D-LF
SERIES | | | LEADFREE
| | | D KEY
| | | 04 WAY
| | | ASSEMBLY
| | | MALE

DESCRIPTION: M12 4PIN(M) D-coded Assembly type