


代碼	SIZE	TOL	代碼	SIZE	TOL
P	1.25	±0.1	S3	6.0	±1.0
TL	100.0	±1(30-100) ±3(101-300)	A	0	0.50max
IL	92.0	±5(301-600) ±8(601-)	CW	0.8	±0.03
TW	36.25	±0.2	CT	0.05	±0.01
TP	33.75	±0.2	Tt	0.17	±0.02
M	1.25	±0.2	T	0.33	±0.03
S1 S2	4.0	±0.5	補強板貼白膜		

Note					
UL Style : AWM 20624 60V 80 °C					
Pitch: 1.25mm					
Pin: 28C					
Length: 100mm					
Conductor: Tinned Copper Tin Plated					
InsulationTh:0.06 PET Color : White					
Support Tape Th:0.225 PET Color : Blue					
Printed YEH CHI E134727 AWM 20624 60V 80 °C VW-1					
TYPE: B TYPE					



FPB-CC28-100-LF  
LEADFREE  
RoHS Compliant

	PART NO. FPB-CC28-100		TOLERANCES ARE .X ± 0.2 .XX ± .XXX ± AWG	DESCRIPTION:				
	DWG NO. FPB-CC28-100							CHECKED BY CY
焜倫股份有限公司	FILE NO.		DRAWING BY		AREA	REVISIONS	HK	DATE
	UNIT / mm	SCALE 1:1	PROJECTION					