



SPECIFICATIONS

CURRENT RATING : 1 Amp

INSULATOR RESISTANCE : 5000 MΩ MIN.

CONTACT RESISTANCE : 20 mΩ MAX.

DIELECTRIC WITHSTANDING : AC 500 V

OPERATING TEMPERATURE : -40°C ~ +105°C

MAX PROCESSING TEMP : 230° FOR 30 SECONDS

CONTACT MATERIAL : PHOSPHOR BRONZE

INSULATOR MATERIAL : POLYESTER UL 94V-0

STANDARD : NYLON-6T

FINISH : TIN, GOLD OR DUPLEX PLATED

STANDARD : GOLD FLASH ALL OVER

NOTE :

DUPLEX PLATING : GOLD PLATED ON CONTACT AREA,
TIN ON SOLDER AREA

MORETHANALL
CONNECTORS
ASSEMBLIES

煜倫有限公司

PART NO. S-R67-2Xxx

DWG NO. S-R67-2Xxx

FILE NO. 200D-2-xxGR-1

UNIT / mm

SCALE 1:1

APPROVED BY CY

DRAWING BY

PROJECTION

TOLERANCES ARE

.X ±0.30

.XX ±0.20

.XXX ±0.10

AWG

DESCRIP TION:

2.0mm Female Header 90° Type

AREA

REVISIONS

HK

DATE