

- 1.SHELL: MATERIAL:BRASS, C2680 THK=0.3±0.01.
FINISH: 60u" NI PLATED.
- 2.CONTACT: MATERIAL:PHOSPHOR BRONZE
JIS 5191R-H,THK=0.2±0.01.
FINISH: 3u" MIN GOLD FLASH ON CONTACT AREA
120u" MIN SN-PB ON SOLDER TAIL AND
60u" MIN NI UNDERPLATED ON ENTIRE CONTACT.
- 3.HOUSING: MATERIAL: LCP+15%GF,UL 94V-0.
- 4.GENERAL TOLERANCE: ±0.15

4	SHELL	PHOSPHOR BRONZE(C5191)	NICKEL PLATED	1	
3	INSULATOR	LCP	BLACK	1	
2	PIN B	PHOSPHOR BRONZE(C5191)	30U"GOLD/TIN	4	
1	PIN A	PHOSPHOR BRONZE(C5191)	30U"GOLD/TIN	4	
Item	Name	Material	Finish	Q'ty	Note

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

X.±

CHECKED BY GENIUS

.X±

UNIT / mm

SCALE 1 : 1

.XX±


DATE

.XXX±

ANG ±

SIZE A4

PJECTION



ORDER INFORMATION

MSB-PS-8C-LF
SERIES | LEADFREE
8 PIN C TYPE
SOLDER
MALE

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: MiniUsb 8PIN (M) 雙排 (方形)