


MATERIAL AND FINISH:

NO.	DESCRIPTION	MATERIAL	FINISH
1	HOUSING	LCP	COLOR:BLACK
2	CONTACT	COPPER ALLOY	CONTACT AREA:AU
3	SWITCH A[Vss]	COPPER ALLOY	
4	SWITCH B[Vdd]	COPPER ALLOY	FLAT AREA: AU OR SN
5	PLATE	SUS	
6	SLIDER	LCP	COLOR:BLACK
7	COIL SPRING	SUS	
8	LOCK PIN	SUS	

PIN NO.	DESCRIPTION
# 1	DAT2
# 2	CD/DAT3
# 3	CMD
# 4	VDD
# 5	CLK
# 6	VSS
# 7	DAT0
# 8	DAT1
# 9	ANT1
# 10	ANT2

CIRCUIT OF SWITCHES:



Notes :

1. Coplanarity of contacts and plate are 0.1MAX.
2. There is no problem in the quality to remain some lubricant on the surface of products.
3. There is a possibility of changing about detailed shape and materials.
4. The shaded portion in figure shows the range of operation of the switch[vss] When the card is inserted, please install the clearance of 0.3mm to avoid electric contact.
5. The diagonal area in drawing is a pattern prohibition area, separately, make a arrangement for details.

RoHS Compliant

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES
煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1


DATE

SIZE A4

TOLERANCES ARE

X, ±
.X ±
.XX ±
.XXX ±
ANG ±

PJECTION



ORDER INFORMATION

TFC-WPBE14B-08-LF
SERIES | LEADFREE
08WAY
B TYPE
EAR TO EAR 14.3mm
90°SMT | BOTTOM CONTACT
PUSH PUSH

DESCRIPTION: Micro SD Socket