



SPECIFICATIONS

Current Rating: 2A AC,DC
 Voltage Rating: 250V AC,DC
 Temperature Range: -25°C ~ +85°C
 Contact Resistance: 30mΩ Max.
 Insulation Resistance: 1000MΩ Min.
 Withstanding Voltage: 800V AC/minute
 Pin Material: Brass/Gold-flash
 Material: Nylon 6T,UL94V-0
 Cap: Nylon 6T,UL94V-0,Natural(Beige)
 Color: Natural(Beige)

Ordering Information & Dimensions

PART NO.	Dimensions		
	A	B	C
DF11-VPC-2X02	2.00	6.00	4.00
DF11-VPC-2X03	4.00	8.00	6.00
DF11-VPC-2X04	6.00	10.00	8.00
DF11-VPC-2X05	8.00	12.00	10.00
DF11-VPC-2X06	10.00	14.00	12.00
DF11-VPC-2X07	12.00	16.00	14.00
DF11-VPC-2X08	14.00	18.00	16.00
DF11-VPC-2X09	16.00	20.00	18.00
DF11-VPC-2X10	18.00	22.00	20.00
DF11-VPC-2X11	20.00	24.00	22.00
DF11-VPC-2X12	22.00	26.00	24.00
DF11-VPC-2X13	24.00	28.00	26.00
DF11-VPC-2X14	26.00	30.00	28.00
DF11-VPC-2X15	28.00	32.00	30.00
DF11-VPC-2X16	30.00	34.00	32.00
DF11-VPC-2X17	32.00	36.00	34.00
DF11-VPC-2X18	34.00	38.00	36.00
DF11-VPC-2X19	36.00	40.00	38.00
DF11-VPC-2X20	38.00	42.00	40.00

DF11-VPC-2Xxx-LF
 T
 LEADFREE

RoHS Compliant



PART NO. **DF11-VPC-2Xxx**

DWG NO. **DF11-VPC-2Xxx**

CHECKED BY CY

TOLERANCES ARE

DESCRIPTION:

2.00mm PITCH
 180° WAFER - SMT TYPE

FILE NO.

DRAWING BY

.X ± 0.2
 .XX ±
 .XXX ±
 AWG

AREA

REVISIONS

HK

DATE

煜倫股份有限公司

UNIT / mm

SCALE 1:1

PROJECTION