


Straddle P.C.B. Layout(T=1.0mm)

**NOTES**

**\*Material**  
 Housing: LCP, UL 94V-0 Rated, Color: Black;  
 Contact: Phosphor Bronze  
 Plating: Gold Plating Over Nickel on Contact Area; Tin Plating on Solder Tail.

**\*Electrical Specification**  
 Operation Voltage: 100 VAC Max.  
 Current Rating: 1.5 Ampere Per Contact.  
 Contact Resistance: 30 Milliohms Max.  
 Insulation Resistance: 1000 Megohms Min.  
 Dielectric Withstanding Voltage: 500 VAC.

**\*Environmental**  
 Operating Temperature: -55°C to +125°C



煜倫股份有限公司

www.morethanall.com

**RoHS Compliant**

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1


DATE

SIZE A4

TOLERANCES ARE

- X, ±
- .X ±
- .XX ±
- .XXX ±
- ANG ±

PJECTION



**ORDER INFORMATION**

**SATA-SE10-15+07-LF**  
 SERIES | LEADFREE  
 | 15+07 WAY  
 | EDGE CLIP 1.0mm  
 FEMALE

DESCRIPTION: SATA 7+15P Standard Straddle Type(1.0mm)Female