



SPECIFICATION
 CURRENT RATING: 2A AC,DC
 VOLTAGE RATING: 250V AC,DC
 TEMPERATURE RANGE: -25°C TO +85°C
 (INCLUDING TEMPERATURE RISE)
 CONTACT RESISTANCE: INITIAL VALUE/10M OHM MAX.
 AFTER ENVIRONMENTAL TESTING/20M OHM MAX.
 INSULATION RESISTANCE: 1,000M OHM MIN.
 WITHSTANDING VOLTAGE: 800V AC/MINUTE
MATERIAL AND FINISH
 CONTACT: PHOSPHOR BRONZE, TIN-PLATED
 POST: BRASS, COPPER-UNDERCOATED, TIN/LEAD PLATED
 APPLICABLE WIRE: AWG #30 TO #24
 AVAILABLE NUMBER OF CIRCUITS: 2 TO 15
 PC BOARD MOUNTING DIRECTION: STRAIGHT, RIGHT-ANGLE
MECHANICAL PERFORMANCE
 INSERTION FORCE.....280G MAX
 WITHDRAWAL FORCE.....210G
 RETENTION FORCE.....1.2KGF
 DURABILITY(MATING CYCLES)
 TIN-LEAD.....20

B			PART NO. PH-T-24		TOLERANCES ARE	DESCRIP TION:			
			DWG NO. PH-T-24						
A	焜倫股份有限公司		FILE NO.		X. XX. XXX. AWG	AREA			
			UNIT / mm	SCALE 1:1					
								REVISIONS	HK