

Material

- Item (a) Clamp: Brass(CuZn) Ni plated
- Item (b) Terminal screw: Steel Zinc plating "-" slot type
- Item (c) Female contact: PhBz, Tin plated
- Item (d) Terminal Cover: Thermoplastic (UL94V-0)
- Item (e) Terminal housing: Thermoplastic (UL94V-0)

Electrical cULus/VDE/TUV

- Voltage rating: 300VAC/300VAC/300VAC
- Current rating: 20A/20A/20A
- Wire range: 2.5mm²/0.34-2.5mm²
- Solid wire(AWG): 12-24/14-22
- Stranded wire(AWG): 12-24/14-22
- Torque: 5Lb-In/0.5Nm/0.56Nm
- Screw: M3
- Wire strip length: 7-8mm
- Withstanding Voltage: 1.6KV/2.5KV/2.5KV
- Operating temperature: -40°C to +115°C
- Safety Approval: cULus, VDE, TUV
- Use with 0Q1.0x1.0mm square pin, Withdrawal force:200 - 500gf /pole


DIMENSION	Poles	Tolerance	
		DIM A	DIM L&DIM B
L Nx5.08	2p-6p	±0.15	±0.20
A (N-1)x5.08	7p-12p	±0.20	±0.25
B Nx5.08+0.1	13p-18p	±0.25	±0.30
	19p-24p	±0.30	±0.40

N=Number of poles

RoHS Compliant

TOLERANCES ARE

X	± 0.50
.X	± 0.30
.XX	± 0.10
.XXX	±
ANG	± 1°



ORDER INFORMATION

TBH051-SW-xx-LF
 SERIES | LEADFREE
 | 02~24WAY
 | SCREW WIRE
 | FEMALE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY
 CHECKED BY GENIUS
 UNIT / mm SCALE 1 : 1
 DATE
 SIZE A4 PROJECTION

DESCRIPTION: