

RECOMMENDED PCB LAYOUT

规格说明: Specifications:

电气特性: Electrical:

1. 额定电流: Current Rating  
1.0A/contact terminal
2. 额定电压: Voltage Rating  
30V DC
3. 接触阻抗: Contact Resistance  
50 milliohms MAX
4. 耐电压: Dielectric Withstanding Voltage:  
300 V AC AT Sea Level
5. 绝缘阻抗: Insulation Resistance:  
100MEGA ohms MIN

原材料: Raw material:


1. 塑胶: Plastic cement:  
Hing Temperature Thermoplastics,  
LCP Black
2. 端子: Contact: Copper Alloy C2680/ C5191
3. 外壳: Shell: Copper Alloy C2680

电镀: Electroplate:

1. 端子: Contact: Plated Gold in Mating Area;  
Tin On Solder Talls
2. 外壳: Shell:  
Nickel Plating

RoHS Compliant

TOLERANCES ARE



煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm


SCALE 1 : 1

DATE


SIZE A4

X. ± 0.30  
.X ± 0.25  
.XX ± 0.20  
.XXX ± 0.10  
ANG ± 5°

PPOJECTION



ORDER INFORMATION



DESCRIPTION: MINI USB 5P/F 90° B型 (兩腳加長)