


Note:

Specification:

1. Current rating: 0.5 A Max.
2. Dielectric withstanding voltage: 30 V(ac) for 1 minute.
3. Contact resistance: 30 mΩ Max.
4. Insulation resistance: 1000 MΩ Min at DC 500V.
5. Insertion force: 4.5 Kgf Max.
6. Extraction force: 1.0 Kgf Min.
7. Temperature range: -55°C~+105°C



4	Spacer	1	LCP	UL 94-V0	Black
3	Shell	1	Brass	T=0.50mm	80U"min Nickel Plated
2	Contact	19	Phosphor bronze	T=0.25mm	Contact area:0.8u"min Gold Plated over 40u"Nickel min. Solder area:80u"min Tin Plated over 40u"Nickel min. (All Gold)
1	Housing	1	LCP	UL 94-V0	Black
No.	Name	Q'ty	Material	Remarks&Thickness	Finish

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

X, ±
.X ± 0.20

CHECKED BY GENIUS

.XX ± 0.10

UNIT / mm


SCALE 1 : 1

.XXX ±
ANG ±

DATE

SIZE A4

PPOJECTION



ORDER INFORMATION

HDMI-SDZB-19-LF

SERIES | | | | LEADFREE
19WAY
PCB
CLIP
DIP 180°
FEMALE

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: HDMI-19PIN(F) 夾板式