



Dimensional & Ordering Information: $\triangle C$

Circuits	Part No.	Dimensions			Pcs/Bag
		A	B	C	
2	PA-DX-02	—	8.0	7.00	1000
3	PA-DX-03	4.00	10.0		1000
4	PA-DX-04	6.00	12.0		1000
5	PA-DX-05	8.00	14.0	13.60	1000
6	PA-DX-06	10.00	16.0		1000
7	PA-DX-07	12.00	18.0		500
8	PA-DX-08	14.00	20.0		500
9	PA-DX-09	16.00	22.0		500
10	PA-DX-10	18.00	24.0	13.60	500
11	PA-DX-11	20.00	26.0		500
12	PA-DX-12	22.00	28.0		250
13	PA-DX-13	24.00	30.0		250
14	PA-DX-14	26.00	32.0		250
15	PA-DX-15	28.00	34.0		250

Material: *Insulator: Thermal Plasticity Resin UL 94V-0 (Milky Yellow)
 *Contact: Brass, Matte Tin Plated
 Note: RoHS and Halogen Free Compliance

PA-DX-xx-LF
 LEADFREE
 RoHS Compliant

MORETHANALL
 CONNECTORS
 ASSEMBLIES

煜倫股份有限公司

PART NO. PA-DX-xx		CHECKED BY CY	TOLERANCES ARE .X± .XX± .XXX± AWG
DWG NO. PA-DX-xx			
FILE NO.		DRAWING BY	PROJECTION
UNIT / mm	SCALE 1:1		

DESCRIP TION:			
AREA	REVISIONS	HK	DATE