

SPECIFICATIONS

- . Voltage Rating : 250V AC/DC
- . Current Rating : 5A AC/DC
- . Withstanding Voltage : 1,500V AC/minute
- . Insulation Resistance : 1,000MΩ min
- . Temperature Range : -25±C to +85±C
- . Contact Resistance : 20mΩ max

HOUSING

- . Poles : 1- 6
- . Material : Nylon 66 UL94V-0
- . Q' ty : 1,000 pcs./Bag

Poles	Part No.	Dimensions (mm)			
		A	Aa	B	Bb
1	V-H-01	----	----	5.95	----
2	V-H-02	7.50	----	12.55	----
3	V-H-03	----	12.50	----	17.55
4	V-H-04	----	17.50	----	22.55
5	V-H-05	----	22.50	----	27.55
6	V-H-06	----	27.50	----	32.55

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm


SCALE 1 : 1

DATE

SIZE A4

PJECTION

X, ±
.X ± 0.30
.XX ± 0.20
.XXX ± 0.10
ANG ± 1°



ORDER INFORMATION

V-H-xx-LF
SERIES | LEADFREE
01~06 WAY
HOUSING

DESCRIPTION: 5.0mm DISCONNECTABLE CRIMP STYLE CONNECTORS HOUSING