



OPERATION FORCE	
L	100±50g
H	180±50g (std.) (Click sound)



SCHEMATIC



KBSW-DRxx-180-LF
LEADFREE

CAP COLOR	
BK	Black
GE	Gray
BL	Blue
RD	Red
YL	Yellow
GR	Green
OR	Orange

SPECIFICATION

Circuit: PUSH (ON).
Rating: 1A 125V AC.
Insulation resistance: 100MΩ for 500V DC .
Contact resistance: 30mΩ for 1A 5V DC .
Life cycles: 100,000 Cycles.
Withstand voltage: AC 500V 1 minute.
Operating force: 180±50g.
Soldering: 245°C Max for 3 Sec.

MATERIAL

Cover: PC.
Base: Nylon 66 + Glass fiber.
Spring: Stainless steel, heat treatment.
Spring piece: Stainless steel, heat treatment.
End contact: Bronze, gold plated.
End terminal: Carbon-steel, gold plated.

RoHS Compliant



PART NO. KBSW-DRxx-180		CHECKED BY CY	TOLERANCES ARE .X ± 0.2 .XX ± .XXX ± AWG	DESCRIP TION:				
DWG NO. KBSW-DRxx-180					DRAWING BY	AREA	REVISIONS	HK
FILE NO.		PROJECTION						
UNIT / mm	SCALE 1:1							

煜倫股份有限公司