

NOTE:

- 1.ELECTRICAL PROPERTIES:
 - 1-1.CONTACT CURRENT RATING:1A AT 250V AC MIN.
 - 1-2.CONTACT RESISTANCE:50m Ohm MAX
 - 1-3.INSULATION RESISTANCE:100M Ohm MIN.
 - 1-4.DIELECTRIC WITHSTANDING VOLTAGE:AC 100V/1 MINUTE.
 - 1-5.MEASURE ENVIRONMENT:TEMP. 21°C/R.H.55%
- 2.MATERIAL:
 - 2-1.CONTACT:PHOSPHOR BRONZE(C5191R-H).
 - 2-2.HOUSING:LCP
 - 2-3.SHELL:PHOSPHOR BRONZE(C5191R-H).
- 3.PLATING:
 - 3-1.TERMINAL: SEE TABLE, GOLD FLISH MIN ON SOLDER TAILS, UNDERPLATED NICKEL OVER ALL 50u" MIN.
 - 3-2.SHELL: NICKEL 60u", SMT GOLD FLISH ON ALL AREA

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

X, ±

CHECKED BY GENIUS

.X ±

UNIT / mm

SCALE 1 : 1

.XXX ±

DATE


ANG ±

煜倫股份有限公司

www.morethanall.com

SIZE A4

PJECTION



ORDER INFORMATION

MSB-SWMEPC-10AB-LF
SERIES | | | | LEADFREE
FEMALE | | | | 10PIN AB TYPE
90°SMT | | MYLAR
POST
METAL EAR

DESCRIPTION: MINI USB 雙排10PIN(F)AB TYPE(前DIP 後SMT)