



1. CONDITION

TEMPERATURE: -40~+70℃
: 95%(40℃)

2. VOLTAGE RATED: DC50V 0.2A

3. CONTACT RESISTANCE: $\leq 0.03\Omega$

4. INSULATION RESISTANCE: $\geq 100M\Omega$

5. WITHSTAND VOLTAGE: AC500V(50Hz)min

6. INSERTION / WITHDRAWAL FORCE: 3~25N

7. LIFE CYCLE: 5000

NO	DESCRIPTION	MATERIAL	FINISH	QTY
5	CENTER PIN	BRASS	Sn	1
4	BODY	BRASS	Sn	1
3	BRACKET	BRASS	Sn	1
2	INSULATOR	PLASTIC		1
1	TUBE	BRASS	Sn	1

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1:1

DATE

SIZE A4

PPOJECTION

0.5-5 =±0.2
5-30 =±0.4
30-120 =±0.6
120-315 =±1
315-1000 =±1.6
1000-2000 =±2.4



ORDER INFORMATION

PAL-JRC79-75-LF

SERIES | | | LEADFREE
75 OHM
CENTER HIGH 7.9mm
DIP 90°
JACK

DESCRIPTION: FEMALE IEC CONNECTOR