



ELECTRICAL PROPERTIES:

1. 100% Open Short Mis -Wire Test
2. Contact Resistance: 2 ohm max
3. Insulation Resistance: 10mega ohm min
4. Hipot test: DC 100V 10ms

| | | |
|-----|---|------|
| ④ | PVC 45P 黑色 (ROHS) | 12G |
| ③ | MINI USB/M 針G/F 殼鍍鎳 黑膠芯 (ROHS) | 1PCS |
| ② | USB A/M 針G/F 殼鍍鎳 白膠芯 (ROHS) | 1PCS |
| ① | UL2725 #28/1P+#28/2C+AEB (AL) OD:3.5 BLACK (ROHS) | 1PCS |
| NO. | DESCRIPTION | Q'TY |

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1:1

DATE

SIZE A4

X. ±

.X ±

.XX ±

.XXX ±

ANG ±



ORDER INFORMATION

MBUB-8A4A28-M30C-LF

SERIES

LEADFREE

300mm

MALE TO MALE

28 AWG

8 PIN A TYPE TO 4 PIN A TYPE

煜倫股份有限公司

www.morethanall.com

P PROJECTION

DESCRIPTION: USB AM/MINI USB 8P L=30cm