



Materials

- Item a Terminal body: Thermoplastic (UL94V-0)
- Item b Female contact: PhBz(CuSn), Tin plated
- Item c Terminal cover: Thermoplastic (UL94V-0)

Electrical cULus

- Voltage rating: 300VAC
- ⚠ ● Current rating: 20A
- Withstanding Voltage: 1.6kv
- ⚠ ● Operating temperature: -40°C to +115°C
- Soldering temperature: 250°C±10°C/5 Sec
- ⚠ ● Safety Approval: us

Poles	02	03	04	05	06	07	08	09	10	11	12	13	
Dim A	10.16	15.24	20.32	25.4	30.48	35.56	40.64	45.72	50.8	55.88	60.96	66.04	
Dim B	5.08	10.16	15.24	20.32	25.4	30.48	35.56	40.64	45.72	50.8	55.88	60.96	
TOL	±0.15				±0.20				±0.30				
Poles	14	15	16	17	18	19	20	21	22	23	24		
Dim A	71.12	76.2	81.28	86.36	91.44	96.52	101.6	106.68	111.76	116.84	121.92		
Dim B	66.04	71.12	76.2	81.28	86.36	91.44	96.52	101.6	106.68	111.76	116.84		
TOL	±0.30						±0.40						

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X, ±
.X ±
.XX ±
.XXX ±
ANG ±

P PROJECTION



ORDER INFORMATION

TBH051-SD19-xx-LF

SERIES LEADFREE
02-24WAY
HIGH 19mm
DIP 180°
FEMALE

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: