



P.C.Board Layout

HAL-D-xxx-LF  
LEADFREE  
006:6PIN  
068:68PIN  
RoHS Compliant

Circuits	Dimension		
	A	B	C
6	2.54	18.31	8.46
10	5.08	20.85	11.00
12	6.35	22.12	12.27
14	7.62	23.39	13.54
16	8.89	24.66	14.81
20	11.43	27.20	17.35
26	15.24	31.01	21.16
30	17.78	33.55	23.70
34	20.32	36.09	26.24
40	24.13	39.90	30.05
44	26.67	42.44	32.59
50	30.48	46.25	36.40
60	36.83	52.60	42.75
64	39.37	55.14	45.29
66	40.64	56.41	46.56
68	41.91	57.68	47.83

Contact:  
Contact:Brass.  
Insulator:LCP.  
Finish:Gold flash plated over nickel.



PART NO. HAL-D-xxx

DWG NO. HAL-D-xxx

FILE NO.

UNIT / mm

SCALE 1:1

CHECKED BY CY

DRAWING BY

PROJECTION

TOLERANCES ARE

.X ± 0.2  
.XX ± 0.1  
.XXX ±  
AWG

DESCRIP TION: 1.27-1.27 Pitch Shrouded Header Stright Type

AREA	REVISIONS	HK	DATE
------	-----------	----	------

煜倫股份有限公司