



NOTES

***Material:**

Body: LCP, UL 94V-0 Rated. Color:Black
 Contacts: Brass.
 Plating: Gold Plating Over Nickel on Contact Area; Tin Plating on Solder Tail

***Mechanical:**

Insertion Force: 0.74N max per contact pair;
 Withdrawal Force: 0.15N min per contact pair;
 Contact Retention Force: 3.92N min per contact;

***Electrical Specification**

Contact Resistance : 30 Milliohms Max.
 Current Resistance : 1.7 Ampere
 Insulation Resistance : 1000 Megohms Min, At 500V AC.
 Operating Temperature : -40°C to +105°C

E08-VPC-xxx-LF
LEADFREE
RoHS Compliant

項目 PIN 數	DIM 'A'	DIM 'B'	DIM 'C'	DIM 'D'	DIM 'E'
40P	15.20	17.35	20.60	18.20	17.20
60P	23.20	25.35	28.60	26.20	25.20
70P	27.20	29.35	32.60	30.20	29.20

MORETHANALL
 CONNECTORS
 ASSEMBLIES

煜倫股份有限公司

PART NO. E08-VPC-xxx		CHECKED BY CY		TOLERANCES ARE		DESCRIP TION: Edge Card Connector (SMT Type)	
DWG NO. E08-VPC-xxx		DRAWING BY		.X \pm 0.2 .XX \pm 0.1 .XXX \pm AWG		AREA	
FILE NO.	UNIT / mm	SCALE 1:1	PROJECTION			REVISIONS	DATE