

**P.C.B. LAYOUT(REF)**

- NOTES:
1. Rating: 300V 4A (IEC 130V)  
PITCH: 2.54mm
  2. Insulation Withstands Voltage:  
AC 1000 V/MIN
  3. Insulation Resistance:  
500M  $\Omega$  or more at DC500V
  4. Using Temperature Range:  
-40°C~+105°C
  5. Suitable Electric Wire:  
AWG 28~20 (IEC 0.5mm<sup>2</sup>)
  6. Undimensioned Tolerances:

|                          |             |          |           |
|--------------------------|-------------|----------|-----------|
| $\pm$                    | $\Delta$    | $\nabla$ | 0.05/1D   |
| $\perp$                  | $\parallel$ | $\equiv$ | 0.2/1d    |
| PITCH ERROR              |             |          | 0.05/1D   |
| UNDIMENSIONED TOLERANCES |             |          | $\pm 0.3$ |

| ITEM | NAME OF PART | Q'TY | MATERIAL        | NOTES                    |
|------|--------------|------|-----------------|--------------------------|
| 5    | END COVER    | 1    | PA66(V0)        | M001<br><del>GREY</del>  |
| 4    | LEVER        | P    | POM             | W005<br><del>WHITE</del> |
| 3    | CLAMP        | P    | Stainless Steel |                          |
| 2    | SOLDER PIN   | P    | COPPER          | Tin Plated               |
| 1    | HOUSING      | P    | PA66(V0)        | M001<br><del>GREY</del>  |

**RoHS Compliant**

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

DRAWING BY CY

X,  $\pm$

CHECKED BY GENIUS

.X  $\pm$

UNIT / mm

SCALE 1 : 1

.XX  $\pm$


.XXX  $\pm$

ANG  $\pm$

DATE

SIZE A4

P PROJECTION



**ORDER INFORMATION**

**TBX026-A15GE-xx-LF**

SERIES | | | LEADFREE  
| | | 02-24WAY  
| | | GRAY  
| | | HIGH 15.5mm  
| | | SLANT DIP

**煜倫股份有限公司**

[www.morethanall.com](http://www.morethanall.com)

DESCRIPTION: