



Specification

1. Voltage Current Rating: 1.5AMP.30V DC
2. Insulation Resistance: 100MΩ MIN
3. Contact Resistance: 30mΩ Max
4. Dielectric Withstanding Voltage: 500V AC
5. Temperature Range: -40°C to +85°C

1394BI-SWM2P1-09-LF
LEADFREE

RoHS Compliant

ITEM	PART NO	DESCRIPTION	Q'TY	MAT'L	REMARK
4		Outer Shell	1	C2680 T=0.30	TML-Plating:Ni50~80u"
3		Inner Shell	1	C2680 T=0.20	TML-Plating:Ni50~80u"
2		Housing	2	LCP(black)	UL94V-0
1		Contact	9	C2680 T=0.20	TML-Plating:Bottom Ni50~80u"Exterior Au1u"15u"30U"

MORETHANALL
CONNECTORS
ASSEMBLIES

煜倫股份有限公司

PART NO. 1394BI-SWM2P1-09

DWG NO. 1394BI-SWM2P1-09

FILE NO.

UNIT / mm

CHECKED BY CY

DRAWING BY

PROJECTION

SCALE 1:1

TOLERANCES ARE
X. ± 0.20
.X ± 0.15
.XXX ± 0.05
ANG

DESCRIPTION:		AREA	REVISIONS	DATE