

**RECOMMENDED  
CABLE STRIPPING DIM'S**

1. CRIMPED FERRULE HEX CRIMP SIZE .213"
2. CRIMPED CONTACT PIN HEX CRIMP SIZE .042"

7	FERRULE	BRASS	1	NICKEL PLATED
6	NUT	BRASS	1	NICKEL PLATED
5	CONTACT PIN	P-BRONZE	1	GOLD PLATED
4	INSULATOR	TEFLON	1	NONE
3	INSULATOR	TEFLON	1	NONE
2	BODY	BRASS	1	NICKEL PLATED
1	BODY	BRASS	1	GOLD PLATED
ITEM	DESCRIPTION	MATERIAL	Q'TY	FINISHED

**1656-JCPBN-FLEX5-LF  
LEADFREE**

**RoHS Compliant**

**MORETHANALL**  
CONNECTORS  
ASSEMBLIES

PART NO.1656-JCPBN-FLEX5

DWG NO. 1656-JCPBN-FLEX5

CHECKED BY CY

TOLERANCES ARE

DESCRIPTION: 1.6-5.6 FEMALE CRIMP FOR FLEX-5

FILE NO.


DRAWING BY

.X ± 0.2  
.XX ±  
.XXX ±  
AWG

UNIT / mm

SCALE 1:1

PROJECTION



AREA

REVISIONS

HK

DATE

**煜倫股份有限公司**