




P.C.B LAYOUT

PIN	A	B	C
6	15.24	12.94	5.08
8	17.78	15.48	7.62
10	20.32	18.02	10.16
12	22.86	20.56	12.70
14	25.40	23.10	15.24
16	27.94	25.64	17.78
20	33.02	30.72	22.86
24	38.10	35.80	27.94
26	40.64	38.34	30.48
30	45.72	43.42	35.56
34	50.80	48.50	40.64
40	58.42	56.12	48.26
50	71.12	68.82	60.96

MATERIAL

HOUSING : NYLON-6T, UL94V-0

CONTACT : COPPER ALLOYS

SPECIFICATION

CURRENT: 3A

OPERATING TEMPERATURE: -25°C TO +105°C

DIELECTRIC WITHSTANDING : AC 500 V

CONTACT RESISTANCE : 20 MOHM MAX

INSULATION RESISTANCE : 1000 MEGAOHMS MIN

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

PPOJECTION

X, ±
.X ± 0.38
.XX ± 0.25
.XXX ±
ANG ± 5°

照片框

ORDER INFORMATION

B-DD33-xx-LF
SERIES LEADFREE
06~50 WAY
DIP 3.3mm
DIP 180°

DESCRIPTION: B□X HEADER 2.54 180°