



NO	DESCRIPTION	MATERIAL	FINISH	QTY
7	NUT	BRASS	NICKEL	1
6	WASHER	IRON	NICKEL	1
5	PIN	COPPER	TIN	1
4	PIN	COPPER	TIN	1
3	INSULATOR	POM	NONE	1
2	BODY	ZINC ALLOY	NICKEL	1
1	CENTER CONTACT	PHOSPHOR BRONZE	GOLD	1

LOCK WASHER

1/2-28UNEF-2B
CLAMP NUT

RECOMMENDED MOUNTING HOLE
 MAXIMUM PANEL THICKNESS:5.5MM
 RECOMMENDED MOUNTING TORQUE:
 12 INCH-POUNDS MAX

RoHS Compliant

TOLERANCES ARE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1:1

DATE

SIZE A4

X.±
 .X±
 .XX±
 .XXX±
 ANG±

PPOJECTION



ORDER INFORMATION

BNC-JD15WFM-75-LF
 SERIES | JACK | LEADFREE
 | | 75 OHM
 | | FULL METAL
 | | WASHER+NUT
 | | HIGH 15.8mm
 | | DIP 180°

DESCRIPTION: BNC FEMALE PANEL MOUNT