



PIN OUT

P1	CONDUCTOR	P2
PIN		PIN
SHELL	BRAID	SHELL
P3	CONDUCTOR	P4
PIN		PIN
SHELL	SPIRAL	SHELL

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

PPOJECTION

X. \pm
.X \pm
.XX \pm
.XXX \pm
ANG \pm

照片框

ORDER INFORMATION

BNCDCX22-02205926-MExxM-LF

SERIES

02 TO 2.0 Dia

LEADFREE
5M:5000mm
10M:10000mm

26 AWG
RG 59

MALE TO MALE / FEMALE TO MALE

DESCRIPTION: BNC MALE / DC JACK TO BNC MALE / DC PLUG

煜倫股份有限公司

www.morethanall.com

***CONSTRUCTION:

1. CABLE: * RG-59/U(1C/26#+AB50%)+(1C/26#+S55%)*2F
OD:5.0*3.0 BLACK JACKET.

***CONNECTORS:

2. DC JACK: * DC JACK5.5*2.1mm SOLDER TYPE BLACK PBT.
* SHELL: STEEL WITH NICKEL PLATED.
3. DC PLUG: * DC PLUG5.5*2.1*22mm SOLDER TYPE BLACK PBT.
* SHELL: STEEL WITH NICKEL PLATED.
4. BNC: * 75 Ohm BNC CONNECTOR.
* SHELL: STEEL WITH NICKEL PLATED.
* PIN CONTACTS: GOLD FLASH OVER NICKEL.
* INSULATOR: WHITE COLOR POM.
5. HOOD: * MOLDED: BLACK PVC 45P.
6. TEST: * CT: 2 Ohm. IS: 5M Ohm.
7. PACKING: * PACK EACH CABLE IN A POLY BAG.
8. MATERIAL: * MATERIAL WITH RoHS GRADE.

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1:1

DATE

SIZE A4

PPOJECTION 

X.±
.X±
.XX±
.XXX±
ANG±

照片框

ORDER INFORMATION

BNCDCX22-02505926-MExxM-LF

SERIES

2.1mmx5.5mm

LEADFREE
5M:5000mm
10M:10000mm

26 AWG
RG 59

MALE TO MALE / FEMALE TO MALE

DESCRIPTION: BNC MALE / DC JACK TO BNC MALE / DC PLUG