



Note:

1.Material:

- 1.1 Insulator: P.B.T UL 94-V0 rated.
- 1.2 Contact: Brass,t=0.25mm.
- 1.3 Shell: Cold rolled steel,t=0.45mm.

2.Specification:

- 2.1 Current rating: 1 A Max.
- 2.2 Dielectric withstanding voltage: 500 V(ac) for 1 minute.
- 2.3 Contact resistance: 30 mW Max.
- 2.4 Insulation resistance: 1000 MW Min at DC 500V.
- 2.5 Temperature range: -55°C~+105°C

3.Finishes:

- 3.1 contacts:Gold flashed 1u",3u",5u",10U",15u",30u".
- 3.2 Shell: Nickel,tin or Zinc plated.

4	Back-shell		Cold Rolled Steel		
3	Front-shell	1	Cold Rolled Steel	T=0.45mm	Nickel Plated
2	Contact	36	Brass	T=0.25mm	Gold Flashed
1	Housing	1	P.B.T	UL 94-V0	Black/Blue
No.	Part Name	Q'ty	Material	Remarks & Thickness	Finish

CE-P-36-LF  
LEADFREE  
RoHS Compliant

**MORETHANALL**  
CONNECTORS  
ASSEMBLIES

**焯倫股份有限公司**

PART NO. CE-P-36	
DWG NO. CE-P-36	
FILE NO.	UNIT / mm
SCALE 1:1	PROJECTION

CHECKED BY CY	TOLERANCES ARE X. ± .X ± 0.3 .XX ± 0.2 .XXX ± 0.1 ANG ± 1°
DRAWING BY	

DESCRIPTION:	CENTRONIC 36P(M) 夾板1.3		
	AREA	REVISIONS	DATE