



TOLERANCE: ±0.05  
RECOMMENDED P.C.B LAYOUT

#### NOTES: 1. MATERIAL:

1-1 Housing : Engineering plastic , LCP with G.F reinforced , black per UL 94V-0 rate.

1-2 Terminal : Phosphor Bronze , per JIS 5210 , 0.2t

#### 2. PLATING:

2-1 CONTACTS: 0.25  $\mu$  m (10  $\mu$  ") gold plating in contact area.and 2.54  $\mu$  m (100  $\mu$  ") min.

matte Tin in soldering zone, over entire contact underplated with 1.27  $\mu$  m (50  $\mu$  ") min. Nickel over all.

2-2 Solder zone: 2.54  $\mu$  m (100  $\mu$  ") matte Tin, 1.27  $\mu$  m (50  $\mu$  ") min. Nickel underplating over all.

#### 3. RoHS compliant products.

**RoHS Compliant**

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

X, ±

.X ±

.XX ±

.XXX ±

ANG ±

PPOJECTION

照片框

#### ORDER INFORMATION

CFA-PW41AE001-24-LF  
SERIES | | | | | LEADFREE  
MALE | | | | | 24WAY  
90°SMT | | | | | NORMAL  
A TYPE  
POST TO POST 41.82mm

DESCRIPTION: Cfast host\_4.3H 簡易型 (短腳)