



**NOTE:**

- A. Material:**
1. Housing : LCP 30% G.F. , UL94-V0 rated
  2. Contact : Copper ally
  3. Pad : Brass
- B. Plating**
1. Contact : Underplating 50u" min Nickel,  
Contant area 15u" AU over Nickel plated.  
Solder tail 100u" min Sn/Pb over Nickel plated.
  2. Ped : 100u" min Sn/Pb over 50u" min Nickel plated.

Dimension L

Pin type	Circuit No.	Dimensions mm
Detect	1,13,38,50	5.0 ± 0.1
General	2 to 12 , 14 to 24 27 to 37 , 39 to 49	4.25 ± 0.1
Power	25 , 26	3.5 ± 0.1

**PCB Layout**

**MORETHANALL**  
CONNECTORS  
ASSEMBLIES

煜倫有限公司

**PART NO. CFC-PW001XE-50**

**DWG NO. CFC-PW001XE-50**

**FILE NO.**

**UNIT / mm**

**SCALE 1:1**

**APPROVED BY CY**

**DRAWING BY**

**PROJECTION**



**TOLERANCES ARE**

.X ±0.125  
.XX ±0.050  
.XXX±0.010

**DESCRIPTION:**

Compact Flash Card Socket SMT TYPE  
(Standard type fit Type I & Type II CF Card)  
POST L=38.7mm

**AREA**

**REVISIONS**

**HK**

**DATE**