

SPECIFICATIONS

Current Rating: 1A AC,DC
 Voltage Rating: 100V AC,DC
 Temperature Range: $-25^{\circ}\text{C} \sim +85^{\circ}\text{C}$
 Contact Resistance: $20\text{m}\Omega$ Max.
 Insulation Resistance: $1000\text{M}\Omega$ Min.
 Withstanding Voltage: 800V AC/minute
 Material: Nylon 66,UL94V-0

Ordering Information & Dimensions

PART NO.	Dimensions	
	A	B
CT-H-02	2.00	6.00
CT-H-03	4.00	8.00
CT-H-04	6.00	10.00
CT-H-05	8.00	12.00
CT-H-06	10.00	14.00
CT-H-07	12.00	16.00
CT-H-08	14.00	18.00
CT-H-09	16.00	20.00
CT-H-10	18.00	22.00
CT-H-11	20.00	24.00
CT-H-12	22.00	26.00
CT-H-13	24.00	28.00
CT-H-14	26.00	30.00
CT-H-15	28.00	32.00

RoHS Compliant

TOLERANCES ARE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm


SCALE 1:1

DATE

SIZE A4

PJECTION

X, ±
 .X ±
 .XX ±
 .XXX ±
 ANG ±



ORDER INFORMATION

CT-H-xx-LF
 SERIES | LEADFREE
 02~15WAY
 HOUSING

DESCRIPTION: 2.00mm PITCH HOUSING