



Features:

- *All connectors are available 24, 26, 28 AWG copper wire.
- *90° and 180° snap on strain relief cover.
- *Interconnection system for cable to cable application.

General Specifications:

- *Dielectric: Glass filled polyester Recognized UL 94V-0
- *Contact: Phosphor Bronze
- *Plating: Au 20u" min. at mating area; Au 1u" at terminal area, Ni 100u" min. at mating area.

Performance Characteristics:

- *Current Rating: 1A DC/max. per contact pair 1A/max. for simultaneous current on all contacts.
- *Contact Resistance: 25mΩ/Max.
- *Cable A'ssy contact resistance: 70mΩ/Max.
- *Dielectric with standing voltage: AC 1000V
- *Insulation Resistance: 1000MΩ/Min.
- *Temperature Range: -55°C to +125°C

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

X. ± 0.40

CHECKED BY GENIUS

.X ± 0.30

UNIT / mm

SCALE 1:1

.XX ± 0.20

DATE

.XXX ±

ANG ±

SIZE A4

PPOJECTION

照片框

ORDER INFORMATION

CTI-S-64-LF
SERIES | LEADFREE
64 WAY
MALE

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: Ribbon Cable IDC Type Connector 64 Pin Socket