




A	COLOR	C
6	BLACK	4
12	BLACK	5
18	BLACK	6
5	RED	7
3	BLUE	10
1	WHITE	11
2	WHITE	12
22	RED	13
23	RED	14
21	BLACK	15
19	WHITE	18
20	BLUE	19

TWIST

A	COLOR	C
16	WHITE	20
17	BLUE	21
7	WHITE	22
8	BLUE	23
9	BLACK	24
13	WHITE	25
14	BLUE	26
15	BLACK	27
10	WHITE	28
11	BLUE	29

TWIST

TWIST

TWIST

TWIST

NO.	ITEM.	DESCRIPTION	Q'TY
1	WIRE:	UL10064 #32 BLACK	6PCS
2	WIRE:	UL10064 #32 RED	3PCS
3	WIRE:	UL10064 #32 WHITE	2PCS
4	WIRE:	UL10064 #32 BULE	1PCS
5	WIRE:	UL10064 #32 WHITE	5PCS
6	WIRE:	UL10064 #32 BULE	5PCS
7	HOUSING:	FIX-HL-30	1PCS
8	TERMINAL:	FIX-TG-30	22PCS
9	HOUSING:	LV03140-23201	1PCS
10	SHELL:	LV03140T11402	1PCS
11	PULL BAR:	LV03140B50003	1PCS
12	Conductive TAPE:	W:25*L:50	1PCS
13	Acetate TAPE:	W:30*L:60 BLACK	1PCS

NOTES:

1. ALL DIMENSIONS ARE "mm".
2. THE PRODUCT MUST BE COMPLY WITH THE DIRECTIVE OF ROHS.

ELECTRICAL TESTING:

1. 100% OPEN/SHORT TEST
2. CONTACT RESISTANCE: 5mΩ
3. INSULATION RESISTANCE: 5MΩ Min

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm


SCALE 1 : 1

DATE

SIZE A4

PPOJECTION

X. ±
.X ±
.XX ±
.XXX ±
ANG ±



ORDER INFORMATION

CVSFIX-403032-M12C-LF

SERIES

LEADFREE

120mm

MALE

32 AWG

40 TO 30 WAY

DESCRIPTION: CABLE ASS"Y